	ताः ''मिनीस्टील''	सं०
Telegraph	nic Address : "MINISTEEL" No.21013 है 449012	-Admn.Genlo
,	., ., ., ., ., ., ., ., ., ., ., ., ., .	भारत सरकार
	то,	GOVERNMENT OF INDIA इस्पात मंत्रालय MINISTRY OF STEEL
	(As per list enclosed)	उद्योग भवन UDYOG BHAWAN
		नई दिल्ली-110107
		New Delhi-110107 Dated 10 th September, 2012
	Subject: Notice inviting tender Digital Audio Conferencing system in	for supply and Commissioning of the Ministry of Steel.
	Sir,	

The undersigned is directed to invite "sealed cover tenders" from reputed firms for supply and Commissioning of Digital Audio Conferencing system in the Ministry of Steel . If your firm is interested to do this job, then please send your sealed cover tenders to Room No. 64, Udyog Bhawan, "G" wing by 11 AM on 25.09.2012. A tender box will also be placed in front of Gate No 1 reception of Udyog Bhawan for this purpose. A demand draft of 30,000/(payable to "Pay & Accounts Officer, Ministry of Steel) as Earnest Deposit Money should also be enclosed with the tender. The detailed tender documents are enclosed with this letter.

- 2. The competent authority in the Ministry of Steel has all rights to accept or reject any tender or postponing or canceling the tender process without explaining any reasons therefore.
- 3. A copy of this letter is also available on the website (www.steel.nic.in) of this Ministry as well as Central Public Procurement Portal. The interested firm may also contact to the undersigned for any further details in this regard.

Yours sincerely

(S.K.Gupta)

Under Secretary to the Government of India

Tel: 23061243

 \bigvee Copy to: NIC for placing the tender notice on the official website of this Ministry.

Oualifying Criteria

Interested bidders should meet the following qualifying criteria:

- 1. Should have completed successfully two projects of at least 20 lakhs each of audio Integration during the last two years as on 31-March-2012. Documentary proof should be attached.
- 2. Should have had average annual financial turnover of Rs: 10 crore on Audio Integration/related works during the last three years ending 31st March 2012. (i.e. 2011-12, 2010-11, 2009-10). For this purpose bidder's own turnover will be considered not their OEM's.
- 3. Should have authorization from the principal manufacturers for the sale and service of required equipments of Audio Integration.
- 4. Technical compliance by the bidders should be adhered and no obsolete products to be quoted.
- 5. Should provide details of the clients with whom the bidder has done similar work including name, address, e-mail, telephone and fax numbers.
- 6. The sound system manufacturer(OEM) shall have base in India for sales, Service support and Service Centre in Delhi. Documentary proof shall be attached for the same.

*The bid not accompanying above Authorizations shall be rejected.

सुरेन्द्र कुमार्य गुणा/S. K. GUPTA अदर सुचिव/Under Secretary इस्पात मंत्रालग/Ministry of Casel भारत रास्कार/Govi. of India कर्त किन्नकी/Made Decid

TENDER DOCUMENT for

Supply, Installation, Testing, Commissioning and Maintenance of Complete Audio Conference System for Conference Room at Ministry of Steel, Udyog Bhawan, New Delhi

Important dates:

25.09.2012 11AM Last Date for Submitting Tender: Date for Opening of Technical Bid: 25.09.2012 11:30AM

date of opening of Price Bid: Will be intimated on due course.

- 1. Sealed Tenders are Invited for Supply, Installation, Testing, Commissioning and Maintenance of Complete Conference System in Conference Room at Ministry of Steel, Udyog Bhawan, New Delhi. The details can be downloaded from our website steel.nic.in free of cost. It is also available on Central Public Procurement Portal.
- 2. Tender should reach to Shri S.K. Gupta, Unbder Secretary, Ministry of Steel, Room No. 64, G. Wing, Udyog Bhawan, New Delhi-110107 latest by 25.09.2012 by 11AM".

The technical and financial bids should be put in two separate envelopes clearly mentioning thereon technical or financial bids for "AUDIO CONFERENCE SYSTEM AT MINISTRY OF STEEL, UDYOG BHAWAN, NEW DELHI" on respective envelopes. Then the two envelopes should be put in the third envelop clearly superscribed as "TENDER FOR AUDIO CONFERENCE SYSTEM AT MINISTRY OF STEEL, UDYOG BHAWAN, NEW DELHI". Please note that the demand draft/pay order should be placed with the technical bid documents.

- 3. For any clarification, interested firms/agencies may please contact Shri S.K. Gupta, Under Secretary, Ministry of Steel on telephone No. 23061243.
- 4. The dates mentioned above are subject to changes and the bidders shall be intimated in case of any changes.

सुरेन्द्र कुमीर मुप्ता/S. K. GUPTA अवर सचिद/Under Secretary इस्पात मंत्रालय/Ministry of Steel भारत जरकार/Govt. of India नर्द हिल्ली/New Delhi

TERMS & CONDITIONS

- 1. If the vendor is participating as a consortium, Name, address of all the members/technology partners of the consortia need to be clearly mentioned and no change will be allowed during the evaluation of the tender document.
- 2. Subletting/Subcontracting of the work/contract is not allowed.
- 3. The Ministry will examine the credentials of the contracting firms, based on the documents submitted and verification, experience, turnover, list of satisfied clients, financial soundness and certifications etc. and scrutinize the proposal submitted by them.
- 4. Proof of registration of sales tax, registration of service tax, PAN/TIN etc. should be attached along with Tender(alongwith technical bid documents). The details of the agency may be provided like status/registration of agency, any tie-ups with the principals/manufacturers etc.
- 5. The subsequent procurement will be governed by the rules and regulations of Government of India
- 6. Submitting a tender by the bidder does not automatically guarantee that the bidder will be considered for participation in the further process of procurement
- 7. The bidder or its parent and/or subsidiaries / OEM should not have currently been removed, invalidated or suspended by the Government of India, or any legal authorities within the union territory of India and is not under investigation by any of the government organizations.
- 8. The bidder should have no outstanding bankruptcy, judgment or pending legalaction that could impair operating as a going concern
- 9. The bidder should provide a onsite comprehensive warranty of the system supplied. The warranty period should be mentioned clearly. The firm should also indicate arrangement for the maintenance of system after expiry of warranty period. Successful bidder have to submit a performance guarantee equivalent to 20% of the project value the form of bank guarantee or FD in favour of "Pay and Accounts officer, Ministry of Steel".
- 10. The compliance sheet(Annexure-II) duly filled in and may be submitted alongwith the technical bid documents. The financial bid must be quoted strictly in accordance with the proforma as per Annexure III.

न्द्र पूर्णार मुखा । ३. सं हे हि अवर मुखिला । ११ ता इंटराट १ ४ स्पात मंत्रालय । १३ ता इंटराट १ ४ मारत स्टूडाट (Sout of India नर्द दिल्ली / 1 व्यव टेकर

- Ministry of Steel, Udyog Bhawan reserves the right to accept or reject partial, any or all offers without assigning any reason thereof. All
- The proposal and accompanying documents must be either in English or in Hindi language. It must be received no later than 25.09.2012 by 11 AM and be submitted to: Shri S.K. Gupta, Unbder Secretary, Ministry of Steel, Room No. 64, G. Wing, Udyog Bhawan, New Delhi-110107 clearly mentioning "TENDER DOCUMENTS FOR "Supply, Installation, Testing, Commissioning and Maintenance of Complete Conference System for Conference Room at Ministry of Steel, Udyog Bhawan, New Delhi" in sealed envelopes. The price bid and technical bid should be kept separately. Related product catalogues with technical specification sheet should be attached along with the technical bid.

सुरेन्द्र कुमार गृता/S. K. GUPTA अवर् सिनिन/Under Secretary sert जा 1970 (1921 597 1920) इस्पात मंत्रालय/Ministry of Closi भारत सरकार/Govt, of India अस्त्री किस्ती क्षाल 177 (प

TECHNICAL SPECIFICATIONS

Boundary layer Microphone

The microphone shall be miniature boundary layer microphone, small in size, suitable for table surface mounting. It shall have Half-supercardioid polar pattern reduces pickup of background noise, room acoustics and feedback. The Microphone shall have the following Features Phase cohrent cardiod type

Bottom Mounted Three Pin XLR Nominal sensitivity shall be 22 mV/Pa

Maximum SPL shall be 120 dB SPL for 3% THD Low level loudspeaker, automatically muted if a microphone is on

Priority Module for prority feature

Quantity: 24 nos.(may increase or decrease)

Wireless Lavellier Microphone

Multichannel diversity reciever with atleast 10 channels Auto setup for quick & easy setup

Receiver

RF Carrier freq ranges: 500 to 530, 570 to 600, 600 to 630, 650 to 680, 680 to 710, 720 to 750, 790 to 820, 835 to 865 Mhz

Modulation: FM

Audio Bandwidth 37 Hz to 20000 Hz

THD @ 1Khz < 0.35 S/N Ratio > 119 dB-A

Front LCD display with dual antenna

Transmitter

Frequency Response 75 Hz to 20 KHz

Transducer dynamic type

Supercardiod / Hypercardiod Directional Pattern

Sensitivity > 2.5 mV/Pa

Max SPL for 1% THD > 147 dB

LC display for Baterry status display and other information

RF Output max 50mW

OUANTITY: 2 no.

अवर सिविश्यातातः Secretary इस्पात मंत्रालय/Ministry of Stoel

भारत सरकार/ 3017, व । त्रीक नर्न विरली/New Feeb

1/3

Digital Signal Processor

12 Analog Inputs (with 48v Phantom Power per Channel)

8 Analog Outputs

Configurable Signal Processing

Rich Palette of Processing and Logic Objects

48 Channel, Low Latency, Fault Tolerant Digital Audio Bus

Clear Front Panel LED Indication

Bi-Directional Locate Functionality

QUANTITY: 2 nos(This should be compatible with the video

conferencing system and recording system)

Ceiling Speaker

Coaxially mounted 100 mm (4 in) woofer with butyl rubber surround and 19 mm (.75 in) titanium coated diffraction-loaded tweeter.

High power, wide frequency response and low distortion for high sound level capability.

Frequency Range: 80 Hz - 20 kHz

Power Capacity: 80 W Continuous, Program Power: 40 W Continuous Pink

Noise

Rated Maximum SPL: 102 dB @ 1 m (3.3 ft)

QUANTITY: 8 nos.

Line Array Speaker

Constant directivity up to the highest frequencies and reduces outof-coverage lobing.

Switchable voicing provides flat response in music mode or midrange presence peak in speech mode.

Dynamic SonicGuard™ overload protection

50W rms Built-in 70V/100V transformer, plus 8 ohm direct capability.

Components: Eight 50 mm (2 in) Full-Range Frequency range (-10 dB): 80 hz to 20 Khz

Coverage Pattern: Vertical 20° (1.5 kHz - 16 kHz, ±10°) Horizontal

150° (ave, 1 kHz - 4 kHz, ±20°)

Sensitivity (2.83V@ 1m): 93 dB (speech mode, 2 kHz - 14 kHz) 89

dB (music mode, 300 Hz - 18 kHz)

QUANTITY: 4 nos.

2/3

वर सिकारीकान Secretary इस्पात पंजालय/Linisity of Sise भारत सरकार/Govit of India नहें जिन्ही/May Domi

Dual Channel power Amplifier

375 / 300 watt RMS at 8 ohm dual channel.

High Performance, Lightweight Class D amp

Integrated Pure Band $^{\text{TM}}$ Crossover System for better performance and control

 $Peakx^{\text{IM}}$ Limiters provide maximum output while protecting your speakers

XLR, 1/4", RCA inputs provide outstanding flexibility Efficient forced-air fans prevent excessive thermal buildup Electronically balanced XLR inputs; touchproof binding post and Speakon® outputs

Precision detented level controls, power switch, power LED, and six LEDs which indicate signal, clip and fault for each channel

Cables and Connectors:

1.5 sq mm 2 core speaker cable:
As per actualmeasurement
2 core shielded microphone cable:
Quantity: As per actualmeasurement
As per actualmeasurement

Connectors: 1 lot

Equipment rack :of appropriate size for housing the above

equipments: QUANTITY: 1 no.

3/3

सुर्भेद्र कुमार गुन्ता/S. K. GUPTA अवर संख्य/Under George?/ इस्पात मंत्रालय/Ministry of Sissi भारत सरकार/Govt. of India नई दिल्ली/New Peth

FOR TECHNICAL BID(COVER-1) ANNEXURE II COMPLIANCE SHEET

			LIANCE		
+		YES	NO	DEVIATION	
<u> </u>	Boundary layer Microphone				
1	The microphone shall be miniature				
1	boundary layer microphone, small in				
٠,	size, suitable for table surface mounting.	Į			
11	It shall have Half-supercardiod polar				
١,	nattern reduces pickup of background	Ì			
	noise, room acoustics and feedback.	ļ			
- 1	The Microphone shall have the following	•			
	Features			 	
	Phase cohrent cardiod type	-			
	Bottom Mounted Three Pin XLR	ļ		 	
	Nominal sensitivity shall be 22 mV/Pa			ļ	
	Maximum SPL shall be 120 dB SPL for				
	3% THD			 	
	Low level loudspeaker, automatically	:			
	muted if a microphone is on				
	Priority Module for prority feature			 	
				- 	
2	Wireless Lavellier Microphone			 	
	Multichannel diversity reciever with	-			
	atleast 10 channels				
	Auto setup for quick & easy setup				
	Receiver				
	RF Carrier freq ranges: 500 to 530, 570				
	to 600, 600 to 630, 650 to 680, 680 to	.			
	710, 720 to 750, 790 to 820, 835 to 865	'			
	Mhz				
	Modulation: FM		_+		
	Audio Bandwidth 37 Hz to 20000 Hz				
	THD @ 1Khz < 0.35				
	S/N Ratio > 119 dB-A	_			
	Front LCD display with dual antenna				
<u> </u>	Transmitter				
_	Frequency Response 75 Hz to 20 Khz				
-	Transducer dynamic type				
-	Supercardiod / Hypercardiod			_	
	Directional Pattern				

70. 57.15 VIO. 30. 103.11 VIO. 1019 VIO. 30. 103.11 VIO. 30.11 VIO. 30. 103.11 VIO. 30.11 VIO. 30.11

					l	
	Sensitivity > 2.5 mV/Pa		 			
	Max SPL for 1% THD > 147 dB		<u> </u>	+		
	LC display for Baterry status display					
	and other information					
	RF Output max 50mW		 	 		
			 			İ
						İ
3	Processor		 			
	12 Analog Inputs (with 48v Phantom					
	Power per Channel)		<u> </u>	 		
	8 Analog Outputs		<u> </u>			
	Configurable Signal Processing		 			1
	Rich Palette of Processing and Logic					
	Objects To the William I was a second of the William I was a secon		+-			1
	48 Channel, Low Latency, Fault Tolerant					
L_	Digital Audio Bus		 			†
	Clear Front Panel LED Indication		+	-		1
L	Bi-Directional Locate Functionality		+			1
	Approved Make : Bosch / AKG /					
<u></u>	Crown		-	_		1
<u></u>			+			†
4	Ceiling Speaker	ļ		_		-
	Coaxially mounted 100 mm (4 in) woofer					
	with butyl rubber surround and 19 mm]				
	(.75 in) titanium coated diffraction-					
<u> </u>	loaded tweeter. High power, wide frequency response	 	-			1
1	and low distortion for high sound level					1
1	capability.					
-	Frequency Range: 80 Hz - 20 kHz		1			7
<u> </u>	Power Capacity: 80 W Continuous,	 				1
	Program Power: 40 W Continuous Pink					
	Noise					
-	Rated Maximum SPL: 102 dB @ 1 m (3.3	1:				
	ft)					
-		1		T		
5	Line Array Speaker					
13	constant directivity up to the highest					
	frequencies and reduces out-of-coverage					
	lobing.					_
	Switchable voicing provides flat					
	response in music mode or mid-range					
	presence peak in speech mode.					_
	Dynamic SonicGuard™ overload			\bot		
L				`	1	
				4	7)/h.	191 W
	2/3			্যান্ত কর্মা	ANIE E	944.7
	-12		`	्र अंतर साह	Majorian Charles	socery of title!
	9 (%) 978			इस्वात मन	Marines Consultations	r ladis
	***			नारत प	Securition U	-2-5/VL

			1	
	protection			
	50W rms Built-in 70V/100V			
	transformer, plus 8 ohm direct			
	capability.			
	Components: Eight 50 mm (2 in) Full-			
	Range		<u> </u>	
	Frequency range (-10 dB): 80 hz to 20			
	Khz			
	Coverage Pattern : Vertical 20° (1.5 kHz			
	- 16 kHz, ±10°) Horizontal 150° (ave, 1			
	kHz – 4 kHz, ±20°)			
	Sensitivity (2.83V@ 1m): 93 dB (speech			
	mode, 2 kHz - 14 kHz) 89 dB (music			
	mode, 300 Hz - 18 kHz)			
6	Dual Channel power Amplifier			
_	375 / 300 watt RMS at 8 ohm dual		—	
	channel.			
	High Performance, Lightweight Class D			
	amp			
	Integrated PureBand TM Crossover	<u> </u>		
	System for better performance and			
	control			
	Peakx TM Limiters provide maximum	-	-	
	output while protecting your speakers			
	XLR, 1/4", RCA inputs provide	-		
	outstanding flexibility			
	Efficient forced-air fans prevent	 		
	excessive thermal buildup		1	
	Electronically balanced XLR inputs;			
	touchproof binding post and Speakon®			
<u> </u>	outputs	+	 	
	Precision detented level controls, power			
	switch, power LED, and six LEDs which			
	indicate signal, clip and fault for each			
1	channel	.1		

FOR: Name of the person and organization with contact Number with company seal and sign

सुरेन्द्र कुमार पुराप S. R. GUPTA अवर सविवा Inder Secretary () प्र इस्पात मंत्रालय I Ministry of Siell भारत सरकार/Govt. of India नहं विक्ली/Nov Dalla

FOR FINANCIAL BID (COVER-2) ANNEXURE III: PRICE BID

1							
7	Description	Quantity	MAKE AND MODEL	Rate(INR)	Amount(INR)	Tax Amount(INR)	TOTAL AMOUNT(INR)
1	Boundary layer Microphone	22 nos					
2	Wireless Lavellier Microphone	1 no					
3	Processor	2 nos					
4	Ceiling Speaker	8 nos					
5	Line Array Speaker	4 nos	÷				
6	Dual Channel power Amplifier	2 nos					
7	2 Core 1.5 Sqmm Loudspeaker cable(mtr)	As per actual measurement		Per meter			
8	2 core shielded Microphone cable(mtr)	As per actual measurement		Per meter			
9	Connectors	1 lot	_				
10	Equipment rack	1 no			177407.744	, (,
11	Installation, Testing and commissioning	1 job				हुरेन्द्र कुमार पुना/ह अवर सचिव//रू इस्पात गंजाल/Minis भारत सरकार/Gov	KSUPTA Secretary 19/W
	GRAND TOTAL					नइ दिल्ली/New	Dahi
				1			İ

FOR: Name of the person and organization with contact Number with company seal and sign

. .